

Mechanic's Best Friend

The Campbell Hausfeld 120-gallon, 10HP, horizontal, two-stage air compressor (CE8001) is ideal for auto repair facilities and tire repair outlets. This air compressor has a high air flow of 36 CFM @ 90 PSI to power multiple, high-demand air tools. Its industrial-rated NEMA motor operates on three-phase electrical power, driving a long-life, cast-iron, two-stage pump that's designed to deliver more than 15,000 hours* of operation. The pump head and valve plate feature an advanced design with Viton® high-temperature O-rings for superior high-pressure sealing when compared to paper gaskets. For smooth, low-vibration operation, the crankshaft is fabricated of ductile iron and optimally balanced.



This air compressor is designed for



Designed with you in mind

The CE8001 is ideal for auto repair facilities and tire repair outlets

- **Viton® Advantage**

Viton® high temperature o-rings for leak proof sealing. Provides high pressure sealing compared to paper-type gaskets

- **Heavy Duty, Cast Iron Pump**

Oil-lubricated, Two Cylinder Two Stage Pump to increase longevity

- **Oil Site Glass**

Located on the front of the pump, the oil site glass allows for quick and easy tracking of oil levels

- **Safe Operation**

Fully enclosed metal belt guard for protection

Specifications

Model	CE8001
Tank Size	120 Gallon
MAX PSI	175
Horsepower	10HP
Phases	3PH
Voltage	208-230/460V
Amperage	27-24.2/12.2A
CFM@90PSI	36CFM
@175PSI	34.1CFM
Unit Weight	880 lbs
Carton Size	78in X 30in X 56in
UPC	045564627201