

For the Automotive Professional

The Campbell Hausfeld 80-gallon, 7.5 hp, vertical, two-stage air compressor (CE7000) is ideal for auto repair facilities and tire repair outlets. This air compressor has a high air flow of 24.3 CFM @ 175 PSI to power multiple, high-demand air tools. Operating on three-phase electrical power, this air compressor's industrial-rated NEMA motor drives a long-life, cast iron, two-stage pump that's designed to deliver more than 15,000 hours* of operation. The pump head and valve plate feature an advanced design with Viton® high-temperature O-rings for superior high-pressure sealing when compared to paper gaskets. For smooth, low-vibration operation, the crankshaft is fabricated of ductile iron and optimally balanced.



Designed with you in mind

The CE7000 is ideal for auto repair facilities and tire repair outlets.

- Viton® Advantage**
 Viton® high temperature o-rings for leak proof sealing. Provides high pressure sealing compared to paper-type gaskets
- Heavy Duty, Cast Iron Pump**
 Oil-lubricated, Two Cylinder Two Stage Pump to increase longevity
- Oil Site Glass**
 Located on the front of the pump, the oil site glass allows for quick and easy tracking of oil levels
- Safe Operation**
 Fully enclosed metal belt guard for protection

Specifications

Model	CE7000
Size	80 Gallon
Horsepower	7.5HP
MAX PSI	175
Free Air CFM	25.0 @ 90PSI 24.3 @ 175 PSI
Voltage	230 Volt
Phase	1PH
Amperage	31A
Unit Weight	585 lbs.
Carton Size	35in x 44in x 84in
UPC	045564625948

This air compressor is designed for



*based on B-10 bearing rating