

For the Automotive Professional

The Campbell Hausfeld 80-gallon, 7.5 hp, vertical, two-stage air compressor (CE7001) is ideal for auto repair facilities and tire repair outlets.

This air compressor has a high air flow of 25 CFM @ 90 PSI to power multiple, high-demand air tools. Operating on three-phase electrical power, this air compressor's industrial-rated NEMA motor drives a long-life, cast iron, two-stage pump that's designed to deliver more than 15,000 hours* of operation. The pump head and valve plate feature an advanced design with Viton® high-temperature O-rings for superior high-pressure sealing when compared to paper gaskets. For smooth, low-vibration operation, the crankshaft is fabricated of ductile iron and optimally balanced.



Designed with you in mind


The CE7001 is ideal for auto repair facilities and tire repair outlets

- **Viton® Advantage**
Viton® high temperature o-rings for leak proof sealing. Provides high pressure sealing compared to paper-type gaskets
- **Heavy Duty, Cast Iron Pump**
Oil-lubricated, Two Cylinder Two Stage Pump to increase longevity
- **Oil Site Glass**
Located on the front of the pump, the oil site glass allows for quick and easy tracking of oil levels
- **Safe Operation**
Fully enclosed metal belt guard for protection

Specifications

Model	CE7001
Size	80 Gallon
MAX PSI	175
Free Air CFM	25.0 @ 90PSI 24.3 @ 175 PSI
Horsepower	7.5HP
Phases	3PH
Voltage	208-230/460V
Amperage	19.8-17.9/9.9A
Unit Weight	585 lbs.
Carton Size	35in x 45in x 83in
UPC	045564627195

This air compressor is designed for



*based on B-10 bearing rating

