

Mechanics Best Friend

The Campbell Hausfeld 120-gallon, 15 hp horizontal, two-stage air compressor (CE8003) is ideal for auto repair facilities and tire repair outlets. This air compressor has a high air flow of 52.4 CFM @ 90 PSI to power multiple, high-demand air tools. Its industrial-rated NEMA motor operates on three-phase electrical power, driving a long-life, cast-iron, two-stage pump that's designed to deliver more than 15,000 hours* of operation. The pump head and valve plate feature an advanced design with Viton® high-temperature O-rings for superior high-pressure sealing when compared to paper gaskets. For smooth, low-vibration operation, the crankshaft is fabricated of ductile iron and optimally balanced.



This air compressor is designed for



Paint Spraying



Inflation



Sanding &
Grinding



Stapling/Fastening



Nailing



Bolting &
Tightening



Cutting



**based on B-10
bearing rating*



Designed with you in mind

The CE8003 is ideal for auto repair facilities and tire repair outlets.

- **Viton® Advantage**

Viton® high temperature o-rings for leak proof sealing. Provides high pressure sealing compared to paper-type gaskets

- **Heavy Duty, Cast Iron Pump**

Oil-lubricated, Two Cylinder Two Stage Pump to increase longevity

- **Oil Site Glass**

Located on the front of the pump, the oil site glass allows for quick and easy tracking of oil levels

- **Safe Operation**

Fully enclosed metal belt guard for protection

Specifications

Model	CE8003
Tank Size	120 Gallon
MAX PSI	175
Horsepower	15HP
Phases	3PH
Voltage	208-230/460V
Amperage	41.1-37.2/18.6A
CFM@90PSI @175PSI	52.4CFM 50CFM
Unit Weight	895 lbs
Carton Size	78in X 30in X 56in
UPC	045564627225