

## Versatile Air Compressor with Spray Gun Kit

The Campbell Hausfeld, 24L air compressor is ideal for the home garage or workshop. The cast iron oil-lube pump is designed for durability and long lasting reliable performance. With a 2 HP motor, this unit is designed for high quality performance. This air compressor has a 0,09 CMM @ 6.2 BAR and a Max 8,6 BAR.



This air compressor  
is designed for



Inflation



Painting



Stapling/Fastening



Nailing



Bolting &  
Tightening



### Designed with you in mind

The DC240100DI is designed for longevity with a long lasting, oil-lubed pump and ideal for most automotive, furniture, and equipment painting.

#### • Portability

Convenient handle and wheels for increased mobility

#### • Horizontal Orientation

Easy to store underneath a workbench in your garage or workshop

#### • Spray Gun Kit Included

Gravity feed spray gun, 13.5 oz. cup and a 25' PVC Air hose

### Specifications

|                                       |                                           |            |
|---------------------------------------|-------------------------------------------|------------|
| Model                                 | DC240100DI                                |            |
| Tank Capacity - L (Gal)               | 24 (6.3)                                  |            |
| MAX Pressure - Bar (PSI)              | 8.6 (125)                                 |            |
| Motor - KW (HP)                       | 1.5 (2)                                   |            |
| Amperage - A                          | 12                                        |            |
| Voltage - V                           | 120                                       |            |
| Frequency - Hz                        | 60                                        |            |
| Phase                                 | Single Stage                              |            |
| Lubrication                           | Oil-Lube                                  |            |
| Cubic Meter<br>Minute (CFM)           | @2.75BAR (40PSI)                          | 0.13 (4.6) |
|                                       | @6.21BAR (90PSI)                          | 0.09 (3.2) |
|                                       | @8.27BAR (120PSI)                         | 0.07 (2.5) |
| Tank Outlet Size                      | 1/4 in NPT                                |            |
| Unit Weight - KG (lb)                 | 24.7 (54.5)                               |            |
| Net Weight - KG (lb)<br>w/accessories | 25.8 (56.9)                               |            |
| Unit Size - cm (in)<br>(LXWXH)        | 58 X 27 X 61<br>(22.8 X 10.63 X 24.02)    |            |
| Gross Weight - KG (lb)                | 28 (61.7)                                 |            |
| Carton Length - cm (in)<br>(LXWXH)    | 59 X 27.8 X 62.5<br>(23.23 X 10.9 X 24.6) |            |
| UPC                                   | 045564644383                              |            |